

## JWX-10

Jewelry Model Maker



Produce perfect, detailed wax models in just a few hours! Roland has made this daunting task easy with the JWX-10 model maker. As the world's first and only jewelry-specific desktop mill, it makes jewelry design and production faster, easier and more profitable.

Just send your designs to the JWX-10 with bundled CAM software, and get back to the creative side of your business. The stylish desktop device will quietly and automatically turn out precise, castable wax models for rings, pendants, bracelets and charms.

With bundled software and user manuals the JWX-10 is a complete jewelry model making solution. Roland's optional ProtoWizard Jewelry CAM software and unique fixtures makes the entire process a snap. The software wizard guides you step by step from importing an STL file from any Jewelry CAD software to quickly generating precise NC files. ProtoWizard's specially designed 3-sided ring fixture and 360 degree arbor automates the production of even the most complex jewelry models.









## ■ Specifications

## JWX-10 Jewelry Model Maker

<u> </u>			
Acceptable materials			Modeling wax, plastic, wood, epoxy composites
X, Y, and Z operation strokes			Up to 5-1/2 (X) X 4-1/8 (Y) X 4-1/8 (Z) in. [140 (X) x 105 (Y) x 105 (Z) mm]
			$\pm 18 \times 10^{5}$ ° ( $\pm 5000$ rotations)
Maximum angle of rotation			, , , , , , , , , , , , , , , , , , ,
Distance from spindle tip to work plate			Up to 4-15/16 in. (126mm)
Dimensions of workpieces installable on the rotary axis unit			Up to: 3-3/8 in. (85 mm)
Loadable workpiece weight			Up to 8.8 lb (4.0kg)
XYZ-axis motor			Stepping motor
Feed rate			XY-axis: 0.0039 to 1.9 in./s (0.1 to 50 mm/sec.) Z-axis: 0.0039 to 1.1 in./s (0.1 to 30 mm/sec.) A-axis:0.02 to 11.79rpm
Software resolution			0.00039 in./step (0.01 in/step)
Mechanical resolution			XYZ-axis: 0.001 in/step (0.025mm in/step) A-axis: 0.0225 deg.
Spindle motor			DC brushless motor, Maximum 100W
Spindle rotation			Up to 20000 rpm
Tool chuck			Cutter holder (4.36 mm) and collet
Interface			USB connector, sensor connector, rotary axis unit connector, expansion connector
Power supply	Voltage and frequency		AC 100 to 240 ± 10%, 50/60 Hz
	Required power capacity		2.1 A
Power consumption			Approx. 210W
A	level	No-load operation	60 dB (A) or less (According to IS07779)
Acoustic noise		Standby	40 dB (A) or less (According to IS07779)
Dimensions			17-3/8 (W) X 20-3/8 (D) X 21-7/8 (H) in. [440 (W) X 517 (D) X 554 (H) mm]
Weight			88.2 lb (40 Kg)
Operation temperature			41 to 104°F (5 to 40°C)
Operation humidity			35 to 80% (no condensation)
Accessories			Power cord, collet, cutter, sensor cable, chucking knob, work plate (large), hexagonal wrenches, hexagonal screw drivers, spanners, Roland Software Package CD-ROM, MODELA Player4 CD-ROM, user's manual, Roland Software Package and MODELA Player4 installation and setup guides





**Enlarged View** 



Actual Size



**Enlarged View** 



Actual Size



**Enlarged View** 



Actual Size



Roland ProtoWizard takes jewelry making to the next level. The software and fixture bundle quickly generates NC tiles and makes it easy to mill even the most complex designs.



Just secure the wax with ProtoWizard's 3-sided ring fixture and easily mill both sides of a ring, or flip the model and mill up to 60 degrees in both directions.



The ProtoWizard ring arbor lets you cut detailed designs 360 degrees around a ring. Never has ring making been this simple!

Roland reserves the right to make changes in specifications, materials or accessories without notice. Your actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland dealer for details. No guarantee or warranty is implied other than expressly stated. Roland shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products. All trademarks are the property of their respective owners.



Authorized Dealer:

